



“Gheorghe Asachi” Technical University of Iasi, Romania



---

## LANDFILL GAS TO ENERGY CONVERSION FROM ORADEA MUNICIPAL WASTE LANDFILL IN ROMANIA

Gerardo Collaguazo<sup>1\*</sup>, Adrian Badea<sup>1</sup>, Constantin Stan<sup>1</sup>, Tiberiu Apostol<sup>1</sup>,  
Gigel Paraschiv<sup>2</sup>, Zoltán Pásztai<sup>3</sup>

<sup>1</sup>Department of Power Engineering, Polytechnic University of Bucharest, Faculty of Power Engineering,  
313 Splaiul Independentei, 060042 Bucharest, Romania

<sup>2</sup>Biotechnical Systems Engineering Faculty, University “Politehnica” of Bucharest, Bucharest, Romania

<sup>3</sup>SC ECOBihor SRL, Oradea, 327 Matei Corvin Str., Oradea, Romania

---

### Abstract

This paper presents the results of theoretical estimations of the quantity of landfill gas (LFG), as well as of the energy potential of Cell A from the municipal landfill in Oradea city, Romania, based on a mathematical model. Considering three scenarios for LFG recovery according to the capture system efficiency, the following LFG theoretical flows have been obtained: 157 m<sup>3</sup><sub>LFG</sub>/h for 45% recovery efficiency; 209 m<sup>3</sup><sub>LFG</sub>/h for 60% recovery efficiency; and 297 for 85% recovery efficiency, respectively. The current recovery system efficiency based on real data is about 45%. On-site measurements revealed that the LFG composition is 53% methane and 0.72% oxygen, thus, it is suitable for electrical energy generation using internal combustion engines. Consequently, by considering 35% motor-generator system efficiency and previous flows of LFG, the electric energy to be obtained is 299 kW<sub>e</sub>, 398 kW<sub>e</sub>, and 564 kW<sub>e</sub>, respectively. At the same time, the electric energy of 281 kW<sub>e</sub> has been obtained for the real data of the LFG flow of 148 m<sup>3</sup><sub>LFG</sub>/h. Considering that the operating time is 7,446 h/yr; the energy generated for the year 2014 is 2,092 MWh<sub>e</sub>. On the other side, from 2005 to 2030, according to the recovery system efficiency, the total electrical energy generated during this period is 40,222 MWh<sub>e</sub>; 53,630 MWh<sub>e</sub> and 75,975 MWh<sub>e</sub> respectively, and the methane emissions have been estimated for about 1.53 million m<sup>3</sup><sub>CH<sub>4</sub></sub>, which represents 417 thousand of tons CO<sub>2</sub> equivalent, which may be reduced by using LFG for producing electricity.

*Key words:* energy, landfill gas, mathematical models, methane emissions, solid waste

*Received:* February, 2015; *Revised final:* May, 2015; *Accepted:* May, 2015