



“Gheorghe Asachi” Technical University of Iasi, Romania



EFFECT OF CORE LAYER COMPOSITION ON WATER RESISTANCE AND MECHANICAL PROPERTIES OF HYBRID PARTICLEBOARD

Jin Heon Kwon¹, Nadir Ayrilmis^{2*}, Tae Hyung Han¹

¹Department of Forest Biomaterials Engineering, College of Forest and Environmental Sciences, Kangwon National University, 200-701, Chuncheon, Republic of Korea

²Department of Wood Mechanics and Technology, Faculty of Forestry, Istanbul University-Cerrahpasa, Bahcekoy, 34473, Sariyer, Istanbul, Turkey

Abstract

In this study, the effect of raw material formulation used in the core layer on the water resistance and mechanical properties of particleboard made from a mixture of rice husk and wood particles was investigated. For this aim, four series of particleboard core layer were produced from different proportions of rice husk/wood particles, different amounts of urea-formaldehyde (UF) adhesive, low density polyethylene (LDPE), and maleic anhydride grafted polyethylene (MAPE), respectively. The amounts of the LDPE and MAPE in the core layer were gradually increased up to 30 wt% and 6 wt%, respectively, while the amount of the UF adhesive was gradually decreased from 8 to 0 wt%. The water absorption, thickness swelling, and internal bond strength of particleboard were greatly improved by the incorporation of LDPE and MAPE into the core layer. The bending properties of the particleboard improved with increasing the LDPE content up to 20 wt%. The MOR and MOE of the particleboard increased with the incorporation MAPE into the core layer.

Key words: compatibilizer, dimensional stability, particleboard, rice husk, wood

Received: December, 2014; *Revised final:* March, 2015; *Accepted:* March, 2015; *Published in final edited form:* December 2018

* Author to whom all correspondence should be addressed: e-mail: nadiray@istanbul.edu.tr; Phone: 90-212-338 2400; Fax: 90-212-338 2424