Environmental Engineering and Management Journal

January 2019, Vol.18, No. 1, 41-45 http://www.eemj.icpm.tuiasi.ro/; http://www.eemj.eu



"Gheorghe Asachi" Technical University of Iasi, Romania



PRECONCENTRATION OF METHYLENE BLUE WASTEWATER USING THE LAYER CRYSTALLIZATION TECHNOLOGY

Yingjie Dai^{1*}, Yujie Feng²

¹Northeast Agricultural University, School of Resources Environment, 59 Mucai Str., Xiangfang District, 150030 Harbin, China ²Harbin Institute of Technology, State Key Laboratory of Urban Water Resource and Environment, 73 Huanghe Road, Nangang District, 150090 Harbin, China

Abstract

This study was carried out to determine the feasibility of applying a freeze-concentration technique to purify wastewater polluted with dye, such as methylene blue (MB) using a stationary wastewater vessel. In this study, we investigated the impact of freezing temperature, initial MB wastewater concentration and vessel depth upon the removal ratio of MB. Results showed that when the freezing temperature was decreased (from -5 °C to -15 °C), the freezing rate increased. The freezing rate was not significantly affected for the different concentrations of the MB solution. The removal ratios of MB at 0-20 mm of ice layer for the concentrations of MB of 1000 mg/L, 2000 mg/L and 4000 mg/L were 84. 29 %, 82.17 % and 80. 02 % respectively at the freezing temperature of -5 °C.

Keywords: freeze-concentration, MB, ice crystal, removal ratio, wastewater

Received: February, 2015; Revised final: April, 2015; Accepted: April, 2015; Published in final edited form: January, 2019

^{*}Author to whom all correspondence should be addressed: e-mail: dai5188@hotmail.com; yujief@hit.edu.cn; Phone/Fax: +86 451 5519 0825; +86 451 8628 3068.