Environmental Engineering and Management Journal

January 2020, Vol. 19, No. 1, 1-9 http://www.eemj.icpm.tuiasi.ro/; http://www.eemj.eu



"Gheorghe Asachi" Technical University of lasi, Romania



STUDY OF BATCH ADSORPTION OF URANIUM IONS BY MCM-48 MATERIALS SYNTHESIZED AT ROOM TEMPERATURE

Meriem Chabane Sari^{1,2}, Abdelkader Namane^{2*}, Jazia Arrar², Redouane Mélikchi¹, Rabah Kerbachi²

¹Department of Material Process Engineering of the Nuclear Research Center of Draria, BP 43 Sebala, Draria, Algiers, Algeria ²Laboratory of Environmental Science and Technology of the National Polytechnic School, 10 Hassen Badi Avenue, BP 12, 16200 El Harrach, Algiers, Algeria

Abstract

The mesoporous MCM-48 was synthesized at room temperature with different templates such as hexadecytrimethylammonium bromide ($C_{16}TABr$), hexadecytrimethylammonium chloride ($C_{16}TACl$) and dodecyltrimethylammonium chloride ($C_{12}TACl$). The obtained materials were characterized by XRD, N₂ adsorption/desorption, FTIR and SEM techniques, and their performance as uranium adsorbent were investigated. In this framework, the effect of contact time, pH of solution, initial uranium concentration and temperature were investigated in batch reactor.

The results showed that the adsorption process was favorably fitted with the second-order kinetic model and the isotherm obeys to Langmuir model. Moreover, the maximum adsorption capacity of MCM-48 for uranium (VI) was of the order of 160 mg/g. The thermodynamic parameters indicated that the sorption of uranium ions on MCM-48 materials was a spontaneous and endothermic process.

Keywords: adsorption, characterization, MCM-48, synthesis, uranium

Received: January, 2019; Revised final: April, 2019; Accepted: June, 2019; Published in final edited form: January, 2020

^{*} Author to whom all correspondence should be addressed: e-mail: abdelkader.namane@g.enp.edu.dz; Phone: 00213699281573