



“Gheorghe Asachi” Technical University of Iasi, Romania



OPTIMIZATION OF THE ELECTRO-FENTON PROCESS FOR COD REDUCTION FROM REFINERY WASTEWATER

Zainab I. Abbas, Ammar S. Abbas*

Chemical Engineering Department, College of Engineering, University of Baghdad, Baghdad, Iraq

Abstract

This study shows the results of the experimental investigation of refinery wastewater treatment by the electro-Fenton process. The experiments were designed using Taguchi design approach with an orthogonal array (OA) of L₁₆ runs. Four process variables (current density (CD), temperature (T), Fe²⁺ concentration (Fe²⁺), and time (t)) at four different levels were considered for the present design. Regression analysis was performed to predict a correlation for the response function (chemical oxygen demand (COD) reduction efficiency) of the treatment process by the electro-Fenton technique. Analysis of variance (ANOVA) was carried out to verify the significant variables that control COD reduction. Moreover, a linear model analysis was implemented for the signal to noise (S/N) ratios with "larger the better" and for means. Based on S/N ratios and means responses, the operating conditions for optimum COD reduction were: CD = 8 mA/cm², T = 60°C, Fe²⁺ = 0.4 mM, and t = 6 h, at which 87.35% of COD was reduced. ANOVA shows that the operating temperature had the most significant impact on COD reduction efficiency. The R-square value for the predicted COD reduction correlation was 90.00%. Considering ranks based on delta statistics, the relative magnitude of effects of the process variables were: T, Fe²⁺, t, and CD.

Key words: COD reduction, electro-Fenton, refinery wastewater, Taguchi method

Received: October, 2019; Revised final: May, 2020; Accepted: May, 2020; Published in final edited form: November, 2020

* Author to whom all correspondence should be addressed: e-mail: ammarabbas@coeng.uobaghdad.edu.iq; Phone: +9647901307270