



*“Gheorghe Asachi” Technical University of Iasi, Romania*



---

## RECYCLING OF LIGHT-EMITTING DIODE WASTE QUARTZ SAND ACTING AS A POZZOLANIC MATERIAL FOR PORTLAND CEMENT

Kae-Long Lin<sup>1\*</sup>, Kang-Wei Lo<sup>2,3</sup>, Wei-Ting Lin<sup>4</sup>, Ta-Wui Cheng<sup>3</sup>, Wei-Hao Lee<sup>3</sup>

<sup>1</sup>Department of Environmental Engineering, National Ilan University, Ilan City, 260, Taiwan, R.O.C.

<sup>2</sup>Graduate Institute of Engineering Technology, National Taipei University of Technology, Taipei City, 106, Taiwan, R.O. C.

<sup>3</sup>Institute of Mineral Resources Engineering, National Taipei University of Technology, Taipei City, 106, Taiwan, R.O. C.

<sup>4</sup>Department of Civil Engineering, National Ilan University, Ilan City, 260, Taiwan, R.O.C.

---

### Abstract

LED waste quartz sand (LEDWS), which is a prominent by product of the LED manufacturing process, may contaminate the environment because it comprises specific heavy metals (e.g., As and Cu), which are hazardous ingredients to the environment when disposed of improperly. Therefore, this study investigated the use of light-emitting diode (LED) waste quartz sand to partially replace Portland Type I cement (OPC) to evaluate the feasibility of reusing it as a pozzolanic material. The SiO<sub>2</sub>, Na<sub>2</sub>O, and CaO contents in the LED waste quartz sand were 70.37, 16.52, and 9.19%, respectively. The results showed that the LED waste quartz sand met the Taiwan EPA regulatory thresholds. Microstructure analysis techniques, such as mercury intrusion porosimetry (MIP), X-ray diffraction (XRD) and scanning electron microscopy (SEM), were used to measure the LED waste quartz sand-blended cement paste (LEDBCP) samples. Compressive strength analysis of the pastes containing 10 wt.% LED waste quartz sand showed that the LED waste quartz sand not only acts as a pozzolanic material to increase the density of the microstructure but also improves the compressive strength of the pastes. LEDBCP with LED waste quartz sand exhibited higher intensity diffraction peaks corresponding to calcium silicate hydrate and lower intensity diffraction peaks corresponding to portlandite (CH) compared with ordinary Portland cement samples at an early age. The gel porosity and pore sizes of the LEDBCP increased with increases in the proportion of LED waste quartz sand. LEDBCP with 10-20 wt.% LED waste quartz sand provides a paste with good pozzolanic characteristics.

**Keywords:** light-emitting diode, microstructure, pozzolanic material, waste quartz sand

*Received: July, 2019; Revised final: November, 2019; Accepted: December, 2019; Published in final edited form: May, 2020*

---

---

\* Author to whom all correspondence should be addressed: e-mail: [klain@niu.edu.tw](mailto:klain@niu.edu.tw); Phone: +886 9317579; Fax: +886 39364277